

# BETONAC<sup>®</sup>-BVP

## HIGH-RANGE WATER-REDUCING CONCRETE ADMIXTURE

### Product Description

BETONAC<sup>®</sup>-BVP is high efficiency polycarboxylate based super plasticizer and is formulated to extend slump-flow life while offering very high workability concrete without segregation and to achieve high early compressive strength. It enables consistent manufacture of self compacting concrete.

### Uses

BETONAC<sup>®</sup>-BVP is designed to produce high workability concrete and is high efficiency super plasticizer to produce virtually SCC (self compacting-consolidating) concrete, with extremely high levels of workability without segregation.

It is used where ever a delay in setting time will ensure sufficient delivery, easy placement, and compaction such as in HOT WEATHER CONCRETING, where delayed and controlled set will assure sufficient placement time and improve concrete quality.

BETONAC<sup>®</sup>-BVP extends slump life and concrete workability and provides superior concrete surface finish characteristics. It reduces bleeding and segregation where poor sand grading are unavoidable.

It saves cement in the region of 10% to 20%.

BETONAC<sup>®</sup>-BVP can be used to produce concrete with very low water/cement ratios, while maintaining normal levels of workability.

### Advantages

- **Easy pumping** - Improves workability and cohesion and extends setting time.  
BETONAC<sup>®</sup>-BVP also provides protection against delays and stoppages.
- **In-situ piling** - Easy removal of formwork and avoidance of cold joints.
- **Workability** - Virtually self-compacting and self-levelling properties. Speeds placing of concrete and constructionworks.
- **Improved cohesion** - Reduces bleeding and segregation where poor sand grading are unavoidable.
- **Cement saving** -Typically in the region of 10% to 20% and can be higher depending on aggregate used.

### Technical Data

#### Note

BETONAC<sup>®</sup>-BVP complies with ASTM C 494 Type A and DIN EN 934-2. It does not contain chloride.

#### Packaging

210 litre drums and IBC containers

### Application

#### Dosage

Typically between 0.8 to 1.8% of cement weight, but can be adjusted to meet extended spectrum of concrete performance requirements.

It is recommended to add BETONAC<sup>®</sup>-BVP to the concrete mix near the end of batch sequence by automatic dispensing equipment.

LeycoChem LEYDE

## Product Data Sheet

Product No: 01.005/2

### Compatibility

**It is recommended not to use with naphthalene and melamine-based concrete admixtures.**

Pretesting of concrete is recommended to optimize dosage rate, addition times in batch sequencing and concrete performance.

### Legal notes

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

**LEYDE-PRODUCTS** are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale. 01.09.2009

LeycoChem LEYDE