

# BETONAC<sup>®</sup>-FIX MF

## HIGHLY EFFECTIVE CEMENT, LIMESCALE AND CONCRETE REMOVER



- Quickly cleans areas contaminated with cement and concrete
- Fast working time
- Almost odourless - no fumes
- Integral degreaser - wide application
- Economical - highly concentrated
- Biodegradable

BETONAC®-FIX MF is a proven cleaning agent for the fast cleaning of flagstones, tiles and slabs as well as ready-mix trucks, cement carriers and all building plant equipment involved in using cement or concrete

The carefully combined cleaning raw materials, specialist defreasers, inhibitors and the combination of salts and phosphoric acid create an outstanding cleaning product, that quickly gives outstanding cleaning results.

BETONAC®-FIX MF cannot be used on glass



**BETONAC®-FIX MF**

Product-No. 02.055

## HIGHLY ACTIVE CEMENT LIMESCALE AND CONCRETE REMOVER

### DESCRIPTION

BETONAC®-FIX MF is a light green, clear, strong acid. Carefully formulated cleansing raw materials, special grease removers and inhibitors and the combination of Salt and phosphoric acid produce a fast acting effective cleaner. The available tensides are biodegradable and the concentrate is almost odourless.

### ADVANTAGES

- Economical – dilutes with water
- Fast acting – saving time
- Almost odourless - causes minimal irritation
- Degreasing action – leaves a brighter finish
- Highly biodegradable

### INSTRUCTIONS FOR USE

BETONAC®-FIX MF is a concentrate and should be diluted with water between 2 and 10 times depending on the degree of contamination of the surface to be cleaned.

Application is by means of a brush. Where there are heavy deposits repeated applications might be necessary. The cleaning action is visible by the foaming reaction on contact with the contaminations of concrete or cement. If the foaming stops further applications are needed until the surface is cleaned. After cleaning the surfaces must be well rinsed with water.

### TECHNICAL DATA

Colour:	Green
Form:	Liquid
Specific Weight::	1,10
pH Value:	< 0,5
Klarschmelzpunkt:	35°C
Contents:	Hydrochloric acid, phosphoric acid, biodegradable tensides

### IMPORTANT INFORMATION

Due to the acid content in the product BETONAC®-FIX MF must not be stored or transported in metal containers. Do not use on Enamel painted surfaces. Test the sensitivity of the surface prior to use.

### PRECAUTION

BETONAC®-FIX is irritant to eyes, skin and breathing. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye / face protection.

### REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

09.01.2004

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com