

LEYCO[®]-LS 5

ACID SPRAYING CLEANER



- Quickly removes rust, limescale, industrial grime, grease and boiler scale
- Also for cleaning natural stone facades, stone linings, metal surfaces and all hard surfaces
- Works automatically
- Non flammable
- Economical - dilute with up to 30 parts water
- UBA-No.: 0595 - 0003

LEYCO®-LS 5 is designed for the removal of rust, limescale, industrial grime, grease and boiler scale. Moreover LEYCO®-LS 5 can clean heavily soiled natural stone facades, stone linings, metal surfaces, wheels and almost all hard surfaces.

LEYCO®-LS 5

Product-No. 20.112

ACID SPRAYING CLEANER

DESCRIPTION

LEYCO®-LS 5 is a water soluble liquid that contains a mineral acid cleaner base, with degreasers and emulsifying agents.

BENEFITS

- strong cleaning efficiency
- flame resistant
- works automatically
- economical – highly concentrated

TECHNICAL DATA

Density: 1,07 g/cm³
Appearance: red
Dilution: 1:2 to 1:30
pH value: 1,0

APPLICATION

For use on metals

Depending upon the application, dilute between 1:2 and 1:30 with water. Apply with brush, hand sprayer pressure cleaner and leave it to react for approx. 1 minute. Once it has reacted, wash off with clean water (preferably using a high pressure cleaner).

For use on stone

When LEYCO®-LS 5 is applied to stone, the surface that needs treating should be moistened with water before the LEYCO®-LS 5 solution is applied. The Solution should be applied by high pressure sprayer, allowed to react for up to 1 minute and then washed off with plenty of clean water.

IMPORTANT NOTE

LEYCO®-LS 5 should not be used on limestone substrates such as marble and terazzo or on enamel, aluminium, glass and zinc galvanized surfaces.

It is recommended that a test is done on a small area, before it is widely used.

STORAGE

Protect from frost.

Store in a cool dry place.

Keep containers away from naked flame.

Minimum shelf-life 30 months.

PRECAUTIONARY MEASURES

Avoid contact with skin and eyes.

Rinse splashes off skin with plenty of clean water.

Wear suitable PPE - refer to the data sheet for details.

UBA-No.: 0595 - 0003

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

09.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com