

LEYCO[®]-SOL 111

SMELL-FREE COLD CLEANING FLUID



- Cold cleaning fluid for use in workshops, for cleaning engines and heavily oiled and greasy parts
- Biodegradable
- Does not create foam
- Universally applicable
- Preserves painted surfaces

LEYCO®-SOL 111 is predominantly used for the cleaning of engines, transmissions, machine parts, turning lathes, boat and aircraft engines, tractors, construction machines, forklift trucks as well as dirty installations into workshops and gas stations. It has very strong grease dissolving properties and therefore works well in the hardest of conditions.



LEYCO®-SOL 111

Product-No. 20.194

SMELL-FREE COLD CLEANING FLUID

DESCRIPTION

LEYCO®-SOL 111 has very high cleaning strength for use on heavily oiled and ancient machinery.

LEYCO®-SOL 111 contains no tensides, Detergents or emulsifying agents and therefore does not form an emulsion with water.

LEYCO®-SOL 111 consists of mix of hydrocarbons that offers extraordinarily high cleaning strength through the use of special additives.

BENEFITS

- Limits the waste water
- biodegradable
- high cleaning ability
- does not create a foam
- universally applicable

TECHNICAL DATA

Density:	0,75 g/cm ³
Appearance:	colorless, clearly
Dilution:	none
Flash point:	65°C
Aromatics content:	<0,5 %

APPLICATION

LEYCO®-SOL 111 is applied with the use of a brush, sprayer, cloth. Once it has reacted on the surface for a short time is washed off with the use of a pressure washer.

STORAGE

Protect from frost. Store in a cool dry place. Protect from fires and in carefully sealed containers.
Minimum shelf-life 30 months.

PRECAUTIONS

Avoid contact with eyes and skin. Splashes immediately with much clear water rinse off. Use rubber gloves.

LEYCO®-SOL ST contains flammable materials, do not spray into open fire. **Do not smoke whilst using. LEYCO®-SOL 111 does not cause corrosion to aluminium or cast iron.** Painted surfaces are not attacked. Always refer to the safety data sheet prior to use.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

09.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com