



*ZETOLAN-AT is simple, safe
and convenient*

ZETOLAN-AT has been developed through close co-operation with our business partners in the construction industry.

Join the Industry Leaders who have profited from the positive benefits of our Market Leading range of Maintenance Chemicals

ZETOLAN[®] -AT

ENVIRONMENTALLY FRIENDLY, ANTI-ADHESION AGENT FOR PROBLEM FREE USE ON BITUMEN AND ASPHALT MIXING PLANT



ZETOLAN-AT is ideally sprayed sparingly and evenly on to surfaces where bitumen and asphalt will affect before starting work.

ZETOLAN-AT acts as a protective film and cleaning agent for asphalt mixing machinery and plant and can be applied neat to all surfaces which come into contact with asphalt - metal, glass, enamelled finishes, rubber. As a cleaning product ZETOLAN-AT has a good cleaning action and can be applied in most areas. Due to its good biodegradability and solvent free nature ZETOLAN-AT is the ideal choice for use in today's health conscious workplaces.

- Does not impair Asphalt quality
- Biologically degradable
- Solvent free
- No oil aerosol
- Simple / Safe / Convenient



ZETOLAN®-AT

- Does not impair Asphalt quality
- Biologically degradable
- Solvent free
- No oil aerosol
- Simple / Safe / Convenient

ZETOLAN®-AT

Product-No. 10.060

PROTECTION FOR CONCRETE MIXERS AND CONSTRUCTION EQUIPMENT

DESCRIPTION

ZETOLAN®-AT is a low viscosity, biologically degradable anti-adhesion agent which prevents asphalt and bitumen from sticking to mixers, recycling machines and all such plant and equipment used in the process. ZETOLAN®-AT in addition to its excellent anti-adhesion properties, can be used also as a cleaning product for the strong smelling products which damage health currently in use.

ADVANTAGES

- Biologically degradable (CECL -33-A-93)
- Does not impair Asphalt quality
- Solvent free
- No oil aerosol
- Environmental classification according to RAL-U264

TECHNICAL DATA

Colour:	Clear Liquid
Viscosity:	40°C 5.0mm ² /s
Specific Gravity:	825 gr
Ignition temp:	140°C
Density:	15°C 825kg/m ³
Neutralisation no:	8.0mg KOH/G
Biodegradability:	95% after 21 days
WGK:	1
pH-value:	neutral

WARNING NOTICE

ZETOLAN®-AT has a high ignition point but should not be sprayed into an open flame. ZETOLAN®-AT is not a "hazardous product".

STORAGE

Store in original sealed containers.
The containers must be protected from contamination by water during storage.

HEALTH AND SAFETY PRECAUTION

Do not drink or spray into open Flames.
ZETOLAN®-AT is not explosive and does not contain solvents.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.
LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale. 21.12.2009

For more information please contact:

Phone: +49 2236 966 00 34

LeycoChem LEYDE

www.leyde.com