

Product Data Sheet

Product No: 10.025

Application

Method of application

Apply a thin but even film by high pressure or any sufficient methods prior to starting work. Even in ready-mix concrete plants all equipment will be protected against contamination for at least one day. After finishing work, remaining concrete, mortar or bitumen can be removed by a jet of water before applying a new film. In case of minor use, protection may last as long as several days.

Important Note

ZETOLAN®-MEK Plus 3 has been developed to protect construction equipment, machinery and vehicles from contaminations and weather as simply and economically as possible in order to guarantee their constant availability. However, in case of cured concrete on surfaces, a product is needed which can dissolve these sediments chemically and not by means of aggressive and damaging methods. In such cases we would recommend to use our products BETONAC®-BL or ZE-KA-FIX® (concrete removers).

Safety Instructions

Safety precautions

Do not drink or spray into open flames. ZETOLAN®-MEK Plus 3 is not explosive and does not contain solvents.

Legal notes

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale. 01.09.2009