

# BETONAC<sup>®</sup>-ZN

## CONCRETE AND RUST REMOVER FOR USE ON AND AROUND GALVANIZED PARTS



- Inhibitors are used to protect galvanized areas which have no detrimental effect on the cleaning capacity
- A variety of applications - construction equipment, formwork, tools, vehicles, pipes and stands
- Quickly and easily dissolves areas of concrete, rust, limescale and calcium
- Highly active concentrate
- Cuts working time
- Economical - diluted up to 10 times with water

BETONAC®-ZN is designed to remove concrete, limescale, boilerscale and rust from construction equipment, formwork parts, tools, vehicle panels and concrete moulds.

It is designed for use around zinc and galvanized parts, which can be attacked by other caustic solutions



## BETONAC®-ZN

Product-No. 02.062

### CONCRETE AND RUST REMOVER FOR GALVANIZED AREAS

#### DESCRIPTION

BETONAC®-ZN is designed to clean machinery and in particular zinc parts that cannot be cleaned with other caustic cleaners. BETONAC®-ZN has special inhibitors that protect the zinc parts during the prescribed application time.

#### ADVANTAGES

- Economical – comes in concentrated form
- Short impact time
- Highly active
- Easy to use

#### TECHNICAL DATA

Density: 1,52 g/cm<sup>3</sup>  
Colour: Colourless  
Dilution: 1:5 bis 1:10  
pH Value: 0,5

#### APPLICATION

BETONAC®-ZN should be mixed 1:5 to 1:10 with water and used for dipping parts in to.

Parts should be dipped for between 30 minutes and 4 hours, depending on the degree of contamination.

If a false floor is placed on the bottom of the dipping container, any washed contamination can easily be removed, so the BETONAC®-ZN is not neutralized and can work more efficiently, and on numerous occasions.

#### HEALTH AND SAFETY INFORMATION

Use BETONAC®-ZN in a well-ventilated area, wear suitable PPE and refer to material safety data sheet.

Tin, Zinc, brass, nickel, galvanized parts and precision instruments as well as hydrocarbon hardened shovels should not be dipped.

BETONAC®-ZN will neutralize with use, though regard for local water authority regulations should be taken when disposing of the used product.

#### STORAGE

Store in a cool dry place, protect from frost.

Min. shelf life 30 months.

#### REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

09.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com