

LEYCO[®]-FR 100

**INTENSIVE ALCALIC CLEANER
FOR HEAVY VEHICLES,
MACHINES USED IN
CONSTRUCTION INDUSTRY
ETC.**



- Dissolves and removes heavy deposits of dirt created by grease and oil, as well as soot and ensilage deposits
- Does not create emulsions in waste water
- Economical product – diluted with water in proportion of up to 1:50

LEYCO®-FR 100 is a strong alcalic concentrate with extremely powerful cleaning function. Owing to its superb effect, it dissolves and removes heavy deposits of dirt created by grease and oil, as well as deposits of soot and ensilage deposits.

Composition of LEYCO®-FR 100 is specially adjusted, so that it does not create emulsions in the system of waste and usable water, the product may therefore be classified as easily conductible.



LEYCO®-FR 100

Product-No. 20.532

INTENSIVE CLEANER FOR HEAVY VEHICLES, MACHINES USED IN CONSTRUCTION INDUSTRY ETC.

DESCRIPTION

LEYCO®-FR 100 solves all problems with cleaning of the exterior of heavy vehicles – trucks, construction vehicles, ensilage vehicles and cisterns. The product may also be used for intensive cleaning of machines and containers. It is also intended for shipbuilding industry.

ADVANTAGES

- Dissolves and removes heavy deposits of dirt created by grease and oil, as well as soot and ensilage deposits
- Does not create emulsions in waste water
- Economical product – diluted with water in proportion of up to 1 : 50
- Biodegradable

TECHNICAL INFORMATION

Density (20°C): ~ 1,08 kg/ l (1 l = 1,08 kg)

pH value: ~ 13

USE

Optimal effect of LEYCO®-FR 100 is obtained if the product is sprayed over the surface which is being cleaned. The product should be diluted with water in advance – mixing ratio 1:3 to 1:20. Several minutes after you have applied the solution (approximately 3-5 minutes), wash the surface with a strong water jet or a jet under pressure.

When applied through a high-pressure device, the product should be sucked in or poured into the existing reservoir for the cleaner; dosing of the product in the jet, depending on the quantity of dirt, should be set to between 1:25 and 1:50 (0,25 - 0,2%).

Do not apply the product to sun-heated surfaces. Always apply the product to the surface from the bottom upwards, in order to avoid straps. Apply carefully to repainted surfaces and old red paint (test before use).

PRECAUTIONS

Freezing does not affect the quality of the product.

Water pollution class:

WGK 2 = heavy pollutant (producer's estimation)

WGK 1 = light pollutant (producer's estimation)

Easily dissolvable in the sewerage system if used in prescribed concentration.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

02.03.05