

LEYCO[®]-PROTECT 10

SEALING WAX



- Protect all types of surface from concrete and mortar adhesion
- Cleaning times are effectively reduced as cleaning becomes much easier
- Safer working practices as acid are used less
- Environmentally friendly
- A gloss finish is left
- The vehicle is protected against rust
- The protective coat lasts upto 4 weeks

LEYCO®-PROTECT 10 is used on coaches, trucks, cement silo trucks, ready-mix concrete mixers, construction machines, and all machinery which is used in external areas.

LEYCO®-PROTECT 10 is suitable for all water-steady surfaces. A high gloss surface is placed upon badly weathered and oxidized surfaces. Plastic bumpers maintain their gloss and look more fresh.

LEYCO®-PROTECT 10 can be easily removed with LS-3.



LEYCO®-PROTECT 10

Product-No. 20.162

WATER BASED SEALING WAX

DESCRIPTION

LEYCO®-PROTECT 10 is a micro sealing wax used to seal the painted surfaces of vehicles. It can also be sprayed upon floors to provide a wearing surface that protects the underlying substrate.

LEYCO®-PROTECT 10 forms a hard and skid-proof protective film, which protects against corrosion and which substantially simplifies cleaning.

LEYCO®-PROTECT 10 leaves a gloss protective film which does not need polishing.

BENEFITS

- very good temporary corrosion protection
- high gloss surface
- substantial simplified cleaning
- simple application

TECHNICAL DATA

Density: 1,0 g/cm³
Color: milk-industrial union/white
Form: liquid

APPLICATION

LEYCO-PROTECT 10 is applied in a thin and even film to the freshly cleaned surface. Either a handsprayer, cloth or brush can be used for this purpose, but a sprayer can give the best finish. For large surfaces a sprayer is recommended. Treat smaller surfaces with a sponge or brush. After around 4 weeks wash the surface with LEYCO-RASANT 2 or LS-3 and then reapply the layer of LEYCO-PROTECT 10.

STORAGE

Store out of frost! Minimum shelf-life 30 months.

PRECAUTIONS

Do not cause vomiting if ingested.

Immediately seek medical advice and present them with the label.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

15.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com