

LEYCO[®]-RASANT 2

FAST ACTING TRAFFIC FILM REMOVER FOR ALL VEHICLES



- Cleans dirt automatically and leaves an electrostatic sealing film
- High cleaning force
- Stops the need to spend time scrubbing
- Economical - mixed with up to 30 parts water
- Phosphate-free
- Pollution free - 90 per cent of the Tenside are biodegradable

LEYCO[®]-RASANT 2 is an automatic cleaner, which quickly removes the traffic film, grease, wax and organic residue that settles on to vehicles and tarpaulines.

LEYCO[®]-RASANT 2 removes an electrostatic sealing film and helps to protect against exhaust gases, diesel smoke, dust and carbon.

LEYCO[®]-RASANT 2 will protect against further recontamination of vehicles.

LEYCO[®]-RASANT 2 is particularly suitable for the freight forwarding business, transporters, buses and all public means of transport. Tanker, silo and refuse lorries, construction machines, ready-mix concrete mixers, excavators, cranes, containers, power lift trucks, campers and all types of vessels.

LEYCO[®]-RASANT 2 can also be used to prepare surfaces before they are repainted or treated.



LEYCO[®]-RASANT 2 Product-No. 20.173

FAST ACTING TRAFFIC FILM REMOVER FOR ALL VEHICLES

BENEFITS

- Strong cleaning action. Leaves an electrostatic film which protects against future dirt
- saves working time - no scrubbing
- highly concentrated - dilute with 5 - 30 parts water
- pollution free - the cleaning tensides in LEYCO[®]-RASANT 2 are over 90% biodegradable. It contains no phosphates and is not combustible.

TECHNICAL DATA

Colour:	clearly / green-yellowish
Spec weight:	1.04
pH value:	approx. 13
Storage:	Protect from frost. Shelf life over 12 months in sealed containers
Note:	Not combustible

OPERATING INSTRUCTION

Wet the surfaces that need cleaning with LEYCO[®]-RASANT 2.

LEYCO[®]-RASANT 2 should then be mixed between 1:5 and 1:30 with water, and sprayed on to the surface from the bottom up. Leave the product to react on the surface but do not allow it to dry. Then rinse off with plenty of clean water. Rinse off from the top working down. This avoids streaking.

In car washes the LEYCO[®]-RASANT 2 should be mixed at a ratio of 1:5 so that the final dilution when sprayed is at 1:10.

When used in steam cleaners the dilution of LEYCO[®]-RASANT 2 can be lower than 1:30, up to 1:50, but again wash off with plenty of clean water and do not allow the material to dry.

IMPORTANT NOTES

Vehicles should be never washed in a frost or strong sunlight.

Never allow LEYCO[®]-RASANT 2 to dry.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

09.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com

LeycoChem LEYDE