

# LEYCO<sup>®</sup>-SEAL 22

## GLOSS SEALING



- Highly durable floor sealer
- Cuts down on rubber tracks
- Very hard floor covering with elasticity
- Leaves a surface shine
- Reduces future contamination
- Simple application
- Manually and mechanically applicable
- Biodegradable

LEYCO®-SEAL 22 is used as a highly durable floor covering on conventional floor substrates. It reduces the amount of black rubber marks left by all types of vehicle, especially fork lift trucks on industrial concrete floors. The surfaces will have a glossy appearance and should help to prevent further build up.



## LEYCO®-SEAL 22

Product-No. 20.192

### HIGHLY DURABLE GLOSS SEALER

#### DESCRIPTION

LEYCO®-SEAL 22 is a metal-interlaced hard wearing floor covering that offers the end user exceptional durability and aids future cleaning.

#### BENEFITS

- Extreme hardness and elasticity
- Simple application
- Reduces rubber deposits
- Manually and mechanically applied
- Biodegradable

#### TECHNICAL DATA

Density:	1,02 g/cm <sup>3</sup>
Appearance:	milky
Dilution:	none
pH value:	8,5

#### APPLICATION

LEYCO®-SEAL 22 is applied according to the porosity of the underlying surface. A maximum of 3 coats should provide protection on even the most porous surfaces.

A mop of cloth will provide the best form of application

Between each application a curing time of at least 3 hours should be provided, to ensure penetration into the deeper pores.

#### STORAGE

Protect from frost. Avoid naked flame.

Store in sealed containers.

Min. Shelf-life 30 months.

#### PRECAUTION

Avoid contact with skin and eyes.

Immediately wash off any splashes to the skin.

Wear suitable PPE.

#### REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

09.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com