

LEYCO[®]-SOL BI

TAR AND BITUMEN CLEANER



- Special solvents remove tar, bitumen, Macadam and some Synthetics are effectively loosened and removed
- Not aggressively - does not attack rubber, concrete, wood or metals
- Easy to apply - no special application machinery is necessary
- Saves Time and Costs - works immediately after application

LEYCO®-SOL BI loosens bitumen and tar from metal surfaces, discharge pipes, brickwork, road finishing machinery and vehicles, bitumen injectors, tools and painted areas. LEYCO®-SOL BI can also be used to remove the tar on roofs and in buildings.



LEYCO®-SOL BI

Product-No. 20.195

TAR AND BITUMEN CLEANER

DESCRIPTION

LEYCO®-SOL BI is a mixture of highly effective solvents, emulsifying agents, boundary surface-active substances and special inhibitors.

BENEFITS

- special solvents remove tar, bitumen, Macadam and some Synthetics are effectively loosened and removed
- Non aggressive to rubber, concrete, wood or metal easy to apply - no special machinery required
- Fast and affective - low labour costs
- Single application is enough

TECHNICAL DATA

Density:	0,85 g/cm ³
Appearance:	colorless, clearly
Dilution:	normally used as a concentrate, when more easily contaminations dilute with petroleum or diesel.
Flash point:	> 60°C

APPLICATION

Preparation

Start by removing heavy deposits from the area, by mechanical means. This accelerates the cleaning process and reduces the quantity of LEYCO®-SOL BI required.

Normal application

LEYCO®-SOL BI is applied with a hand sprayer, scrubbing brush or brushed directly on to the areas which need cleaning. After approximately 20 minutes, wash the area down with a strong water jet, so that the dissolved dirt and LEYCO®-SOL BI is removed. If applied to a lacquered surface of a vehicle, allow less impact time.

Application in the dip

Tools, barrows, bucket, parts of road finishers etc. are put into the covered dip and cleaned after a short reaction time with water jet, high pressure cleaner, brush or brush.

Note

On concrete surfaces which are heavily contaminated, it is often better to sandblast the surface to achieve the desired effect.

STORAGE

Protect from frost/fire. Store in sealed containers.
Min shelf life 30 months

PRECAUTION

Avoid contact with skin and eyes. Wash splashes off skin with plenty of clean water. Wear suitable PPE. Avoid smoking whilst using and naked flame.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale.

09.01.04