# LEYCO<sup>®</sup>-SPL

# RESIN REMOVER FOR USE IN DIPS

- Removes resin from alkali resistant surfaces when used as a dip in ultrasonic baths as well as in special automatic washing machines
- Economical- can be used with 3 - 10 parts water depending on degree of contamination
- Fast, effective and thorough
- Does not produce harmful vapours
- Easily handled liquid composition
- UBA-No.: 0595 0050











LEYCO<sup>®</sup>-SPL is used to remove heavy deposits of resin from surfaces when they are dipped in a solution of it, or when it is applied through specialist high pressure washers.

LEYCO<sup>®</sup>-SPL works extremely fast, thorough and economical, since it can be diluted with 3 to 10 parts water.

Due to its special composition the LEYCO<sup>®</sup>-SPL does not develop dangerous vapors.





## LEYCO<sup>®</sup>-SPL

## HEAVY DUTY RESIN REMOVER

#### **AREAS OF APPLICATION**

LEYCO<sup>®</sup>-SPL is used as a dilution in dips as a heavy-duty resin remover. It is used in ultrasonic baths as well as in special automatic washing machines.

#### DESCRIPTION

LEYCO<sup>®</sup>-SPL is a concentrated, strongly alkaline cleaner with wetting agents and dirt removing additives.

#### BENEFITS

- fast working
- economical
- no dangerous vapors
- easy handling liquid form

#### **TECHNICAL DATA**

Density:	1,36 g/cm <sup>3</sup>
Appearance:	brownishly, clearl
Dilution:	1:3 to 1:10
pH value:	14

#### **APPLICATION**

LEYCO<sup>®</sup>-SPL can be diluted with 3 to 10 parts water depending on the degree of pollution.

LEYCO<sup>®</sup>-SPL can be used in the dipping process in ultrasonic baths, as well as in special automatic washing machines.

#### STORAGE

Do not store with acids or acid based products. Keep in tightly sealed containers. Minimum shelf-life 30 months.

#### PRECAUTION

LEYCO<sup>®</sup>-SPL causes veraetzungen. Keep out of reach of children. Keep away from food and drink. Wear suitable PPE, including eye protection. Immediately rinse off any splashes to the skin or eyes with plenty of clean water.

UBA-No.: 0595 - 0050

#### REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteded against defective materials and manufacture and are sold subject to its standard terms and conditions of sale. 09.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne, Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11, email: leycochem@leyde.com, internet: www.leyde.com