



*ZETOLAN-S ensures
really fair faced concrete*

ZETOLAN-S has been developed through close teamwork with our successful partners in the construction industry.

Profit from the positive experience of your industrial partners or your competition!



ZETOLAN[®]-S

CHEMICAL MOULD RELEASE AGENT

ZETOLAN-S provides quick, clean and easy stripping of moulds and formwork and ensures high quality faced and stain-free concrete.

ZETOLAN-S is a specially formulated agent with chemically release properties which are superior to those of a conventional mould oil. The chemicals react with the water in the concrete to form a thin water-repellent skin on the surface of the mould thereby enabling easy stripping from concrete and acting as a protection to steel and wooden formwork.

- ensures really fair faced concrete
- can be used on all types of mould and shutter faces.
- non-staining
- economical
- minimizes cleaning of shutter before re-use



ZETOLAN®-S

- provides quick, clean and easy stripping of moulds and formwork and ensures high quality faced and stain-free concrete.
- ensures really fair faced concrete
- can be used on all types of mould and shutter faces
- non-staining
- economical
- minimizes cleaning of shutter before re-use

ZETOLAN®-S

Product-No. 10.031

CHEMICAL MOULD RELEASE AGENT

FIELD OF APPLICATION

ZETOLAN-S provides quick, clean and easy stripping of moulds and formwork and ensures high quality faced and stain-free concrete.

DESCRIPTION

ZETOLAN-S is a specially formulated agent with chemically release properties which are superior to those of a conventional mould oil. The chemicals react with the water in the concrete to form a thin water-repellent skin on the surface of the mould thereby enabling easy stripping from concrete and acting as a protection to steel and wooden formwork.

ADVANTAGES

- ensures really fair faced concrete
- can be used on all types of mould and shutter faces.
- non-staining
- economical
- minimizes cleaning of shutter before re-use.

APPLICATION

Using either a brush or any conventional mould oil sprayer, apply one coat of ZETOLAN-S evenly over the entire surface. On metal, glass fibre or other impervious surface one coat is sufficient. On new plain timber surfaces, a further coat of ZETOLAN-S should be applied before placing concrete if the mould is not used within 2-3 days.

New Moulds: No preparation is necessary.

Used Moulds: All traces of cement must be removed together with any surface deposit of previous oils

STORAGE

Keep in a cool and frost free place in tightly closed containers. Store away from fire.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale. 09.07.2009

For more information please contact:

XANTHOS NEMITSAS LTD

Tel.: +357 25 780 018

GSM: +357 99 652288 or +357 99 382262

LeycoChem LEYDE

www.leyde.com